

NITRIFICATION AND DENITRIFICATION PROCESS

Patent Number: JP59142897
Publication date: 1984-08-16
Inventor(s): HARA NORIO; others: 02
Applicant(s): ATAKA KOGYO KK
Requested Patent: ☐ JP59142897
Application Number: JP19830014770 19830201
Priority Number(s):
IPC Classification: C02F3/34; C02F3/08
EC Classification:
Equivalents: JP1581824C, JP2007718B

Abstract

PURPOSE:To reduce power consumption for fluidization and to reduce stripping off of adhered microorganisms by treating filthy water contg. N compds. by a fluidized medium process by suspending vermiculite as a carrier for the microorganism in a reaction vessel.

CONSTITUTION:Filthy water is introduced through a feeding pipe 7 into a denitrification tank 1 where it is allowed to contact with vermiculite particles 4 contg. deposited microorganisms by the lifting effect of the air supplied from an air dispersing pipe 9, and aerated. Nitrified treated water overflows from a nitrifying tank 1 into a separating cylinder 11 in a separating section 5, and the vermiculite 4 is settled and returned to the nitrifying tank 1 from the bottom of the separating section 5. In a denitrifying tank 2, the vermiculite is fluidized in an anaerobic condition by a stirrer 13 and denitrification is performed. Methanol is supplied from a methanol tank 14 as a nutrient for the denitrifying bacteria. Denitrified water is aerated in a reaeration tank 3 by the air from an air dispersing pipe 19.

Data supplied from the esp@cenet database - I2